Declaration of performance

COSMOFIN FG 1,5mm

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

01020401152 (5)

COSMOFIN FG 1,5mm

INTENDED USE OR USES

Plastic and rubber damp proof sheet including basement tanking: type T

MANUFACTURER

WOLFIN Bautechnik GmbH
Am Rosengarten 5, 63607 Wächtersbach Neudorf
Germany

SYSTEM OR SYSTEMS AVCP

System 2+

HARMONISED TECHNICAL SPECIFICATION

EN 13967:2012

NOTIFIED BODY/IES

1213 SKZ
Friedrich-Bergius-Ring 22, 97076 Würzburg

The performance of the product identified above is in conformity with the set of declared performance/s. This declaraton of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wächtersbach Neudorf 6.3.2020

Christian Birck
Managing Director
Region Central Europe

DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	**Class E**
watertightness at 2kPa	NPD
watertightness at 60kPa	Pass
Tensile strength longitudinal	≥ 1100 N/50 mm
Tensile strength transverse	≥ 1000 N/50 mm
Elongation longitudinal	≥ 15 %
Elongation transverse	≥ 15 %
resistance to static load method B	≥ 20 kg
Resistance to impact method A	≥ 600 mm
Resistance to impact method B	≥ 1000 mm
resistance to tearing	≥ 200 N
shear resistance of joints	≥ 800 N/50 mm
durability against artificial ageing/degradation: watertightness at 2kPa	NPD
durability against artificial ageing/degradation: watertightness at 60kPa	Pass
durability against chemicals: watertightness at 2kPa	NPD
durability against chemicals: watertightness at 60kPa	Pass
Dangerous substances	NPD

Note 1: The product contains no hazardous substances
Note 2: In case of non-availability of a harmonised European test specification, test or agreement, national methods are used provisionally.
NPD: No performance determined

WOLFIN Bautechnik GmbH
Am Rosengarten 5
63607 Wächtersbach Neudorf
T +49 6053 708-0
F +49 6053 708-5130
bmigroup.com/de