# Declaration of performance

# EshaBase 460 EW

## **UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE**

#### 0461.4

EshaBase 460 EW

### **INTENDED USE OR USES**

Bitumen membrane for waterproofing

#### **MANUFACTURER**

**ICOPAL BV** Hoendiep 316, 9744 TC Groningen Netherlands

# **SYSTEM OR SYSTEMS AVCP**

System 2+

#### HARMONISED TECHNICAL SPECIFICATION

EN 13707:2013

#### **NOTIFIED BODY/IES**

0620

The performance of the product identified above is in conformity with the set of declared performance/s. This declaraton of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

# Signed for and on behalf of the manufacturer by:

Groningen 01-02-2021



## **DECLARED PERFORMANCE**

ESSENTIAL CHARACTERISTICS	PERFORMANCE
External fire performance	F roof *
Reaction to fire	Class F
Watertightness	Pass (10 kPa)
Tensile strength longitudinal	550 ± 20% N/50 mm
Tensile strength transverse	300 ± 20% N/50 mm
Elongation longitudinal	20 ± 15 %
Elongation transverse	35 ± 15 %
Root resistance	NPD
Resistance to static load method A	NPD
Resistance to static load method B	NPD
Resistance to static load method C	NPD
Resistance to impact method A	NPD
Resistance to impact method B	NPD
Resistance to tearing	100 -0/ +250 N
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability UV heat and water	NPD
Durability: heat flow after heat oven exposure	NPD
Durability: flexibility at low temperatur after heat oven exposure	NPD
Flexibility at low temperatures	≤ -5 °C
Dangerous substances	Note 1&2

Note 1: This product does not contain asbestos or tar constituents

Note 1: In the absence of European harmonized test methods, verification and deklaration on release/content has to be done taken into account national provisions in the place of use.

\*\*since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone



Hoendiep 316 9744 TC Groningen Phone: +31 50 551 6333