

# Declaration of performance

## Icopal Universal SA 3,1mm (EN 13956)

### UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

1104.2

Icopal Universal SA 3,1mm (EN 13956)

### INTENDED USE OR USES

Plastic and rubber sheet for roof waterproofing

### MANUFACTURER

ICOPAL BV  
Hoendiep 316, 9744 TC Groningen  
Netherlands

### SYSTEM OR SYSTEMS AVCP

System 2+

### HARMONISED TECHNICAL SPECIFICATION

EN 13956:2012

### NOTIFIED BODY/IES

0620

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

### Signed for and on behalf of the manufacturer by:

Groningen

01-02-2021



### DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
External fire performance	F roof *
Reaction to fire	NPD
Watertightness	Pass (300 kPa)
Tensile strength longitudinal	≥ 1000 N/50 mm
Tensile strength transverse	≥ 920 N/50 mm
Elongation longitudinal	≥ 20 %
Elongation transverse	≥ 20 %
Root resistance	NPD
Resistance to static load method A	≥ 10 kg
Resistance to static load method B	NPD
Resistance to static load method C	NPD
Resistance to impact method A	≥ 1250 mm
Resistance to impact method B	≥ 1250 mm
Resistance to tearing longitudinal	≥ 300 N
Resistance to tearing transverse	≥ 300 N
Peel resistance of joints	≥ 50 N/50 mm
Shear resistance of joints	≥ 800 N/50 mm
Durability UV heat and water: 1000 h UV	Pass
Durability UV heat and water: 5000 h UV	NPD
Foldability at low temperature	≤ -20 °C
Dangerous substances	Note 1&2

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

\*: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone