

Declaration of performance

VEDATOP SU

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

0394.4

VEDATOP SU

INTENDED USE OR USES

Bitumen membrane for waterproofing

MANUFACTURER

ICOPAL BV
Hoendiep 316, 9744 TC Groningen
Netherlands

SYSTEM OR SYSTEMS AVCP

System 2+

HARMONISED TECHNICAL SPECIFICATION

EN 13707:2013

NOTIFIED BODY/IES

1213

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Groningen

01-02-2021

DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
External fire performance	F roof *
External fire performance	F roof *
Reaction to fire	Class E
Reaction to fire	Class E
Watertightness	Pass (200 kPa)
Watertightness	Pass (200 kPa)
Tensile strength longitudinal	≥ 1000 N/50 mm
Tensile strength longitudinal	1100 ± 20% N/50 mm
Tensile strength transverse	≥ 1000 N/50 mm
Tensile strength transverse	1100 ± 20% N/50 mm
Elongation longitudinal	≥ 2 % abs.
Elongation longitudinal	5 ± 3 % abs.
Elongation transverse	≥ 2 % abs.
Elongation transverse	5 ± 3 % abs.
Root resistance	NPD
Root resistance	NPD
Resistance to static load method A	NPD
Resistance to static load method A	NPD
Resistance to static load method B	NPD
Resistance to static load method B	NPD
Resistance to static load method C	NPD
Resistance to static load method C	NPD

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

*: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone

BMI icopal

Hoendiep 316
9744 TC Groningen
Phone: +31 50 551 6333

icopal.nl